



Specifications	Standards	DURA WOOD
Type of Floorcovering	EN 649 EN ISO 10582	Heterogeneous Heterogeneous
Product Enhancement		PUR
Gauge	EN 428 EN ISO 24346	0.28" 7.0 mm
Wear Level	EN 429 EN ISO 24340	0.028" 0.7 mm
Backing		0.197" 5.0mm
Roll Size	EN 427 EN ISO 24341	6' x 30' = 180ft ² 1.828m x 9.144m = 16.723m ²
Total Weight	EN 430 EN ISO 23997	1.26 lbs/ft ² 6130g/m ²
Static Load Limit	ASTM F970	1280 psi
Residual Indentation	ASTM F970 (MOD)	Pass 0.337 (Ti) - 0.332 (Tf) = 0.005
Abrasion Resistance	EN 649 EN ISO 10582	Backing Type 1
Dimensional Stability	ED 434 EN ISO 23999	±0.40%
Behavior to Fire	ASTM E648	Class 1
Slip Resistance	ASTM D2047	Meets ADA guidelines
Light Fastness	ISO 105-B02 (Method 3)	≥6
Resistance to Chemicals	EN 423 (ASTM F 1303-99)	Excellent
Hygiene	This product has been independently tested and results demonstrate that inhibits the growth of MRSA. An effective cleaing regime is however, the most important defense against infection.	
CHPS 01350	Meets certification guidelines Certified Indoor Air Quality	Pass
Resistance to Light	ASTM F1515	Pass
Resistance to Heat	ASTM F1514	Pass

(877) 496-3566

www.summit-flooring.com