

# PLANKX®

## Product Specification

Pile material	100% Polyamide
Surface	Cut Pile
Wearability	Commercial heavy (33) extreme
Comfort class	LC 1 (standard)

## Environmental & Sustainability

DIBt-AgBB Schema	AbZ.: Z-156.601-36
TÜV PROFiCERT	Lizenz-Nr.: 70 710 3720-3
EPD (Environmental Product Declaration)	EPD-GUT-2009111-D

## Characteristic Features

Width	25 x 100 cm tiles
Primary backing	PES-non woven
Secondary backing	Recyback®
Total weight   with T-Sonic	ca. 3.800 g/m <sup>2</sup>   ca. 4.200 g/m <sup>2</sup>
Total height   with T-Sonic	ca. 6,3 mm   ca. 7,8 mm.
Pile weight	ca. 500 g/m <sup>2</sup>

## Structural Properties

Fire behavior	Cfl-s1
Electrostatic properties	≤ 2 KV
Surface resistance	≤ 10 <sup>9</sup> Ω
Volume resistance	≤ 10 <sup>9</sup> Ω
Impact noise	ca. 24 dB
Sound absorption factor	ca. 0,20



Impact noise with T-SONIC	ca. 25 dB
Sound absorption factor with T-SONIC	ca. 0,30

## Performance Properties

