FACTS & FIGURES

SPECIFICATION DOCUMENT AND SAFETY DATA INFORMATION



DURABELLA 2'x2' Glue Down Terrazzo Tiles











GENERAL

Durabella is made out of various components based on a special modified binder, marble aggregates and/or natural stones. Durabella Biopolymer is made from vegetable oil and is Red List Free. Durabella is a fl xible terrazzo and has a 40% better sound absorption compared to tradional epoxy terrazzo.

FIELD OF APPLICATION

Durabella 2'x2' Glue Down Terrazzo Tiles is an aesthetic, wear-resistant finish for areas with heavy traffic. Suitable for both new construction and renovation (10-18mm) project. Durabella is therefore often used in public buildings such as shopping malls, hotels, receptions, restaurants, convention centers, airports, banks, offices, hospitals, entrance halls, stations, public areas, etc.

LOOK AND FEEL

Very similar to the traditional terrazzo floo s. The surface is smooth. Various patterns and motifs can be obtained in the floo . In contrast to traditional terrazzo oors Durabella can be supplied in RAL, Pantone or NCS colors. The nish can be adjusted to your liking and color composition is customer speci c. Slip-resistance is depending on the finis , multiple options available.

DESIGN

Unlimited possibilities with the color of the binder and the mixing of the aggregates allowing designers to create their own visual. Aectual X Durabella is an innovative and sustainable flooring solutio , created in collaboration with Aectual, combining 3D printed patterns with the Durabella. A novel take on classic artwork terrazzo flooring, ffering endless design opportunities to integrate storytelling in your flooring design.

CHARACTERISTICS

Flexural Strength

Standard: ISO 196-1

10-15 N/mm²

1450-2175 psi

Flexural Strength with Duraforce membrane

Standard: in line with ISO 196-1

20-22 N/mm²

2900-3190 psi

Compressive Strength

Standard: ISO 196-1 (precoated quartz)

40-60 N/mm²

5800-8700 psi

Compressive Strength

Standard: ISO 196-1 (marble)

30-35 N/mm²

4350-7250 psi

Tensile Strength (binder only)

Standard: ISO 196-1

10 N/mm²

1450 psi

Elongation at break (binder only) Standard: ISO 527	Approx. 145% (Base material is 100%)
Binder	Biopolymer
Fire rating	B S1(EN 13501-1)
Color	Unlimited possibilities
Hardness of the binder	Shore D65
Thermal isolation	0,027 m ² x K/W
Underfloor heating	Possible

- Highly UV stable
- 2'x2' Glue Down Tiles
- Easy to clean and maintain
- · Classic elegance
- · Sound absorbing
- Chemical resistant
- Highly resistant to abrasion
- Can be used exterior
- Fast delivery times and high day production
- Can be laid on old surfaces
- Maximum strength and no hairline cracking
- Thickness from 8 to 15mm

Version: 03/2024

