

vertisol	ESSENTIAL WALL	vertisol wall fitnice_
-----------------	-----------------------	----------------------------------

Product Specifications	Standard	ESSENTIAL WALL
Composition	-	85 %vinyl + 15% polyester + backing polypropylene
Weight (g/m²)	-	650 ± 10 %
Thickness (mm)	-	0.84 mm ± 10 %
Light Fastness	EN ISO 105-B02 (blue scale :1-8)	≥ 7/8
Fire Classification	EN 13501-1	B-s2,d0
Abrasion resistance	EN ISO 12947	>100 000 cycles
Roll Width	-	100 cm
Roll Length	-	9 lm
CE Certificate	EN 15102:2007	2895-CPR-SH00885

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications.

The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

Some of the test and certifications present in this TDS can be found under the name Fitnice Wall



ISO 9001:2015 and
ISO 14001:2015
certified company

VERTISOL INT'L SRL
c/ La Volta, 2, Local H2-11
08150 Parets del Vallès, Barcelona
SPAIN
T: + 34 93 840 1444
www.vertisol.com